

Stress plate HTV-82/40



Cross references

DABO® SW8-RT-4.8
DABO® SW8-ET-4.8

Application range

- > To fix roofing membranes and insulating material to substructures made of trapezoidal steel profiles, timber and wood-based materials
- > To fix roofing membranes and insulating material to multi-layer roofing
- > For new buildings
- > For installation with ECOSET tools
- > For manual installation


Properties

- > Alu-zinc-coated steel

Note

For combination with EJOT DABO® screws.

Applications



Certifications



EJOT® installation tool ECOSET available as rental equipment
Article number G000000076



In a functional plastic box

Product online



Order description	Width [mm]	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
HTV-82/40	40	82	500		3020095401	4061245012483

Compatibility acc. to ETA-07/0013

HTV 82/40	SW 8 RT-4.8	SW 8 ET-4.8	TKR-4.8	TKE-4.8	TKR-4-4.8	VHT-R-4.8	VHT-E-4.8	JT2-ST-2-6.0	JT2-ST-2-6.8	JT3-ST-2-6.0	FBS-R-6.3	JBS-R-7.5	FPS-E-8.0	SDF-S-10H-E	SDP-S-10G-E
X	X														