

EJOFAST® self-drilling screw JF3-2H-4.8



Cross references


Socket wrench insert SW8
Cordless screwdriver ASCS 6.3

Application range

- > Side lap stitching of profiled steel / aluminium sheets and sandwich panels

Properties

- > Suitable for installation with the EJOFAST® JF screwdriver
- > A2 stainless steel with hardened steel point
- > Stainless steel sealing washer
- > Pre-assembled sealing washer
- > With free spin zone under screw head for effective side lap stitching
- > Non-skid application
- > Reduced swarf fastening
- > Loose or collated




EJOFAST® JF screwdriver


Rental equipment available
Article number G000000070

EJOFAST

Applications



Technical specifications



Certifications



Product online



Order description	Length [mm]	Clamping thickness [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Sealing washer E 14, Ø 14 mm, loose						
JF3-2H-4.8x19 E14	19	0-4	500		3591977391	4061245015583
JF3-2H-4.8x19 E14 VE100	19	0-4	100		6591977391	4061245014791
JF3-2H-4.8x19 E14 RAL 7016	19	0-4	100		3351977025	4061245039749
JF3-2H-4.8x19 E14 RAL 9002	19	0-4	100		3351977082	4061245039671
JF3-2H-4.8x19 E14 RAL 9006	19	0-4	100		3351977084	4061245044804
JF3-2H-4.8x19 E14 RAL 9007	19	0-4	100		3351977220	4061245044811
Sealing washer E 14, Ø 14 mm, collated						
JF3-2H-4.8x19-E14 collated	19	0-4	500		3385009000	4061245016559
Sealing washer E 16, Ø 16 mm, loose						
JF3-2H-4.8x19 E16	19	0-4	500		3591911391	4061245026466